DMC-F5Digital Camera

Stylish Design and Rechargeable Lithium-ion Battery

5x Optical Zoom from 28mm Wide-angle in a Compact Body

14.1-megapixel CCD Sensor

HD Video Recording with Dedicated Video Button

Auto Scene Selector

Panorama Shot for More Dynamic Images



Compact Digital Camera F5 Featuring Easy Operation

Metrics	
Dimensions (W x H x D)	97.4 x 58.0 x 21.5 mm
	(3.83 x 2.28 x 0.85 inch)
Weight	Approx. 106g without Battery and SD Memory Card (0.23lb)
	Approx. 121g with Battery and SD Memory Card (0.27lb)
Pixels	
Camera Effective Pixels	14.1 Megapixels
Sensor	
Sensor Size / Total Pixels / F	Filter 1/2.33-type CCD Sensor / 14.5 Total Megapixels / Primary Color Filter
Lens	
Aperture	F3.2 - 6.5 / 2-Step (F3.2 / 9.1 (W), F6.5 / 18.4 (T))
Optical Zoom	5x
Focal Length	f=5 - 25 mm (28 - 140 mm in 35 mm equiv.) (34 - 170mm in 35mm equiv. in video recording)
Extra Optical Zoom (EZ)	5.9x (4:3 / 10M), 8.4x (4:3 / 5M), 10.5x (under 3M)
Intelligent Zoom	-
Lens	6 elements in 5 groups
	(3 Aspherical Lenses)
2- Speed Zoom	-

Exposure Compensation

Digital Zoom	Max. 4x
Focus	
Focusing Area	Normal / Auto Scene: Wide 10 cm - infinity / Tele 100 cm - infinity
AF Assist Lamp	-
Focus	Normal
AF Metering	Face / 9-Area / 1-Area
Shutter	
Shutter Speed	8 - 1/2000 sec
Finder	
Viewfinder	-
File	
File Format	Still Image: JPEG (DCF / Exif2.3)
	Motion picture: QuickTime Motion JPEG
Recording Modes	
Mode Dial / Mode Button	Auto SCN, Normal Picture, SCN, Panorama Shot
Creative Control mode	-
Still Image Scene Mode	Portrait, Scenery, Sports, Night Portrait, Night Scenery, Food, Baby(Bir thday only), Sunset, High sensitivity
Continuous Shooting Mode	Full-Resolution Image, approx. 0.5 frames/sec Flash burst shooting
Motion Picture Recordin	g (*2)
HD Video	1280 x 720 pixels, 30fps (HD / Motion JPEG)
STD Video	640 x 480 pixels, 30 fps (VGA / Motion JPEG)
	320 x 240 pixels, 30 fps (QVGA / Motion JPEG)
High Speed Video	-
Continuous recordable t	ime (motion pictures)
AVCHD	-
MP4	-
Actual recordable time (motion pictures)
AVCHD	-
MP4	-
Exposure Parameters	
Exposure	Program AE
	-

1/3 EV step, +/- 2 EV

Auto (AE) Bracketing	-
Light Metering	Intelligent Multiple
ISO Sensitivity	I.ISO / 100 / 200 / 400 / 800 / 1600 High Sensitivity mode (ISO 1600-6400)
Picture Quality	
Still Picture Recording	[1:1] 3232x3232 (10.5M) [4:3] 4320 x 3240 (14M) / 3648 x 2736 (10M EZ) / 2560 x 1920 (5M EZ) / 2048 x 1536 (3M EZ) / 640 x 480 (0.3M EZ) [3:2] 4320 x 2880 (12.5M) [16:9] 4320 x 2432 (10.5M)
Image Quality	-
White Balance	Auto / Daylight / Cloudy / Shade / Incandescent / White Set
Photo Style / Film Mode	-
Color Mode / Color Effect / My color	Color Mode : Standard, Black&White, Sepia
Aspect Bracketing	-
Other	
Digital Red Eye Correction (Red Eye Removal)	- Yes
GPS	
Wi-FI	
NFC	
Zoom in Motion Picture	Yes(Digital Zoom)
Self Timer	2 sec / 10 sec
Display	
Playback Mode	Normal Play, Slideshow, Category Selection, Calendar
Thumbnails / Zoomed Playback	12,30- thumbnails / Yes
Calendar Display / Dual- Image Playback	Yes / No
Set Favorites / Rotate Image	No / No
Show Histogram	-
Show Highlights	
DPOF Print Setting / Set Protect on	i-No / Yes
Edit	
Retouch	-
Resize / Cropping / Aspect Conv. / Leveling	Yes / No / No / No
Copy / Title Edit / Text Stamp	Yes / No / No
Cut Animation	-
Video Divide	-
PictBridge Support	Single / Multi / All

Setup	
OSD language	Japanese, English, German, French, Italian, Spanish
Monitor	
LCD Monitor	6.7cm (2.7") TFT Screen LCD Display (230K dots) Field of View: approx. 100%
Flash	
Built- in- Flash	Auto, Auto/Red-eye Reduction, Forced On, Slow Sync./Red-eye Reduction, Forced Off 0.6 - 5.7m (Wide/i.ISO), 1.0 - 2.8m (Tele/i.ISO)
Media	
Recording Media	Built- in Memory, SD Memory Card, SDHC Memory Card, SDXC Memory Card
Built- in- Memory	Approx. 10MB
Audio	
Microphone / Speaker	Mono / Mono
Interface	
Interface	USB2.0 High speed
Power	
Power	Li-ion Battery Pack (3.6V / 690mAh / 2.5Wh) AC Adaptor (Input: 110-240V AC)(Included, connect with USB cable)
Battery life (approx.)	250 pictures (CIPA Standard)*1
Standard Package	
Included Software	PHOTOfunSTUDIO 9.0 LE, Adobe Reader
Standard Accessories	Battery Pack, AC adaptor, USB Cable, Hand Strap, CD-ROM
NOTE	*1 Recording conditions by CIPA standard - CIPA is an abbreviation of [Camera & Imaging Products Association] Temperature: 23 oC (73.4 oF)/Humidity: 50%RH when LCD monitor is on Using a Panasonic SD Memory Card (32 MB) Using the supplied battery Starting recording 30 seconds after the camera is turned on. (When the optical image stabilizer function is set to [ON].) - Recording once every 30 seconds with full flash every second recording Rotating the zoom lever from Tele to Wide or vice versa in every recording Turning the camera off every 10 recordings and leaving it until the temperature of the battery decreases. *2 - These are standard times taken at a temperature of 23 oC (73.4 oF) and a humidity of 50%RH.

- The time available for recording varies depending on the environment, the interval between recordings, and the manner of use.
- Actual recordable time is the time available for recording when repeating actions such as switching the power supply [ON] / [OFF], starting/ stopping recording, zoom operation etc.
- -Maximum time to record motion pictures continuously with [AVCHD] is 29 minutes 59 seconds.
- -Maximum time to record motion pictures continuously with [MP4] is 29 minutes 59 seconds or up to 4 GB.